





- NOTE:
- 1.Storage Condition:
 - 1.1 Temperature:15 ~ 25°C;
 - 1.2 Humidity :30~60%
 - 1.3 Operation temperature: -30'~+80°C
 - 2.Electrical Characteristics:
 - 2.1 Current rating: 0.1A
 - 2.2 Voltage rating: 60V
 - 2.3 Contact resistance: 320mΩ/meter Max.
 - 2.4 Insulation Resistance: DC500V 1minutes
 - 3.Mechanical Characteristics:
 - 3.1 Durability: 20 cycles
 4. RoHS compliant

		深圳市鑫南天科技有限公司 Shen Zhen Xin Nan Tian Technology Co., Ltd							
		DIMENSIONS UNIT: mm UNLESS OTHERWISE SPECIFIABLE		PRODUCT NAME : FFC cable 0.5pitch 24Pin 250mm length gold finger -same side		DRAWING: COCO		DATE: 2013/09/01	
DIMENSION TOLERANCE X.X: ± 0.25 X.XX: ± 0.20 X.XXX: ± 0.10 ANGULAR: ± 1°		PRODUCT NO. : XNT-FFC24-111141		CHECK: JANY		DATE: 2013/09/01		DRAWING NO. : XNT-1014	
		APPROVED: JEFF		DATE: 2013/09/01		SCALE: 1:1		DWG ID: P D	
				REV.: A		PAGE: 1 of 1			

REVISION NO.	ECR NO.	DESCRIPTION	MARK	DATE
1				
2				
3				