



特性:Specifications:

电器:Electrical:

接触阻抗:Contact Resistance

50 milliohms MAX

耐电压:Dielectric Withstanding Voltage:

100V AC AT Sea Level

绝缘阻抗:Insulation Resistance:

100 MEGA ohms MIN

材料:Material:

塑胶:Housing:Hing Temperature Thermoplastics,  
LCP 耐高温塑胶

端子>Contact: Copper Alloy 铜合金

铜壳:Shell: Copper Alloy 铜合金

电镀:Finish:

端子>Contact: Plated Gold in Mating Area;

Tin On Solder Talls

接触点镀金.脚镀锡

铜壳:Shell:

Nickel/ Plating 镀镍

△				Unless otherwise specified tolerances are 未注尺寸公差		客户 Customer	编号 NO.	HLWD-010	图号 Drawing NO.	设计 Designed by	审核 Checked by	批准 Approved by	共 1 张第 1 张 Sheet 01
				X	±0.3	品名 Item	Mini USB 5P/F四脚贴片式			装配图	刘俊		Third Angle Project 第三角投影
△				X.X	±0.2	版本 REV	材质 Material	厚度 MAT. THICK	数量 Amount	表面处理	交期	单位 Unit	比例 Scale
△	脚高4.05±0.05变更为4.00±0.05	钟少军	08.06.25	X.XX	±0.1	A	C2680	/	/	/	07.**	mm	FREE
	变更内容 Midify content	签名 Sign by	审核 Checked by	日期 Date	X.XXX	±	深圳市鑫南天科技有限公司						
				ANGLES ±° SURFACE TEXTURE									