



NOTES:

1. MATERIAL
  - 1.1 HOUSING: LCP UL94V-0
  - 1.2 TERMINAL: C5191R-H, T=0.20MM
  - 1.3 SHELL: STAINLESS STEEL, T=0.30MM
2. PLATING
  - 2.1 TERMINAL: UNDERPLATING 50U"~80U" NI; SELECTIVE AU 1U"
3. CHARACTERISTICS:
  - 3.1 CONTACT RESISTANCE: 100mΩ MAX,
  - 3.2 INSULATION RESISTANCE: 1000MΩ MIN.
  - 3.3 OPERATION LIFE: 5000 CYCLES
4. PACKAGE:
  - 4.1 TAPE REEL PACKAGE
  - 4.2 700PCS/REEL
  - 4.3 4200PCS/CARTON

B	ECR2017042601	AS MARK	COCO	20170426
A	/	NEW RELEASE	COCO	20160115
REVISION NO.	ECR NO.	DESCRIPTION	MARK	DATE

		<b>深圳市鑫南天科技有限公司</b> Shenzhen XinNanTian Technology Co., Ltd		
		DIMENSIONS INIT: mm UNLESS OTHERWISE SPECIFIABLE	PRODUCT NAME : SIM CARD 6 PIN WITH CD TYPE	DRAWING: COCO
DIMENSION TOLERANCE X.X: ± 0.25 X.XX: ± 0.10 X.XXX: ± 0.10 ANGULAR: ± 1°		PRODUCT NO. : XNT-191S0692WT-1R1	CHECK: AG	DATE: 2017/04/26
		DRAWING NO. : XNT-191S0692WT-1R1	APPROVED: JEFF	DATE: 2017/04/26
		SCALE: NA	DWG ID: P D	REV.: B
				PAGE: 1 OF 1